

Package ‘LTAR’

August 21, 2023

Type Package

Title Tensor Forecasting Functions

Version 0.1.0

Maintainer Kyle Caudle <kyle.caudle@sdsmt.edu>

Description A set of tools for forecasting the next step in a multidimensional setting using tensors. In the examples, a forecast is made of sea surface temperatures of a geographic grid (i.e. lat/long). Each observation is a matrix, the entries in the matrix and the sea surface temperature at a particular latitude/longitude. Cates, J., Hoover, R. C., Caudle, K., Kopp, R., & Ozdemir, C. (2021) "Transform-Based Tensor Auto Regression for Multilinear Time Series Forecasting" in 2021 20th IEEE International Conference on Machine Learning and Applications (ICMLA) (pp. 461-466), IEEE <doi:10.1109/ICMLA52953.2021.00078>.

Depends R (>= 4.2.0)

Imports vars,stats,rTensor, rTensor2, gsignal

License GPL-3

Encoding UTF-8

LazyData true

Config/testthat/edition 3

RoxygenNote 7.2.3

NeedsCompilation no

Author Kyle Caudle [aut, cre],
Randy Hoover [ctb],
Jackson Cates [ctb]

Repository CRAN

Date/Publication 2023-08-21 17:50:02 UTC

R topics documented:

err	2
LTAR	3
LTARpred	4
Ltrans	5
tensor	5

err	<i>Forecast error calculations</i>
-----	------------------------------------

Description

Determines the Frobenius norm between true tensor and the actual tensor.

Usage

```
err(true_tensor, forecast_tensor)
```

Arguments

`true_tensor` : The true tensor from the test set.
`forecast_tensor` : The predicted values from `LTARpred()`

Value

Error: The Frobenius norm between the actual and predictor tensor slices at each forecast step.

Author(s)

Kyle Caudle
Randy Hoover
Jackson Cates

Examples

```
require(rTensor)
data(tensor)
tnsr <- as.tensor(tensor)
tensorTest <- tnsr[,1:2,]
tensorTrain <- tnsr[,3:2000,]
forecast <- LTARpred(p=5, tensorTrain, h=2)
predTensor <- forecast$ypred
errors <- err(tensorTest, predTensor)
errors
```

Description

Fits a Tensor Autoregression (TAR) Model to historical 3D tensor data and returns the coefficient tensor (\mathbf{A}) and the constant matrix (\mathbf{C}).

$$\mathbf{A} = [A_1|A_2|\dots|A_p], \mathbf{C}$$

Usage

LTAR(p,tnsr,type = c("const", "trend", "both", "none"),season=NULL)

Arguments

p : Number of lags
 tnsr : A 3D tensor
 type :Type of deterministic regressors to include.
 season : Inclusion of centered seasonal dummy variables (integer value of frequency).

Value

The coefficient tensor

$$\mathbf{A} = [A_1|A_2|\dots|A_p]$$

and the constant matrix

$$\mathbf{C}$$

for the LTAR model:

$$\mathbf{y}_t = A_1\mathbf{y}_{t-1} + \dots + A_p\mathbf{y}_p + \mathbf{C}D_t + \mathbf{u}_t.$$

Author(s)

Kyle Caudle
 Randy Hoover
 Jackson Cates

References

Cates, J., Hoover, R. C., Caudle, K., Kopp, R., & Ozdemir, C. (2021, December). Transform-Based Tensor Auto Regression for Multilinear Time Series Forecasting. In 2021 20th IEEE International Conference on Machine Learning and Applications (ICMLA) (pp. 461-466). IEEE.

Examples

```
require(rTensor)
data(tensor)
tnsr <- as.tensor(tensor)
# an LTAR(1) model with trend
model <- LTAR(p=1,tnsr,type="trend")
```

 LTARpred

Forecast for a 3D Tensor Autoregression Model

Description

Using a historical 3D tensor, the LTARpred function will forecast h steps into the future.

Usage

```
LTARpred(p, tnsr, h, type = c("const", "trend", "both", "none"), season = NULL)
```

Arguments

p : Number of time series lags
 tnsr : A 3D tensor
 h : Number of steps to forecast
 type : Type of deterministic regressors to include.
 season : Inclusion of centered seasonal dummy variables (integer value of frequency).

Value

A [Tensor-class](#) object which contains the h step forecasts.

Author(s)

Kyle Caudle
 Randy Hoover
 Jackson Cates

References

Cates, J., Hoover, R. C., Caudle, K., Kopp, R., & Ozdemir, C. (2021, December). Transform-Based Tensor Auto Regression for Multilinear Time Series Forecasting. In 2021 20th IEEE International Conference on Machine Learning and Applications (ICMLA) (pp. 461-466). IEEE.

Examples

```
require(rTensor)
data(tensor)
tnsr <- as.tensor(tensor)
result <- LTARpred(p=5,tnsr,h=2,type="trend",season=12)
```

Ltrans *Tensor Transformation*

Description

Performs a tensor transformation of a 3D tensor using the discrete cosine transform along mode 3.

Usage

```
Ltrans(tnsr)
```

Arguments

tnsr : A 3D tensor

Value

a [Tensor-class](#) object that has been transformed using the DCT.

Author(s)

Kyle Caudle
Randy Hoover
Jackson Cates

Examples

```
require(rTensor)
data(tensor)
tnsr <- as.tensor(tensor)
trans_tensor <- Ltrans(tnsr)
# print first lateral slice
trans_tensor[,1,]
```

tensor *Sea Surface Temperatures*

Description

A 5-by-6 grid of sea-surface temperatures from 5 degrees N, 180 degrees W to 5 degrees S, 110 degrees W recorded hourly from 7:00PM on 4/26/94 to 3:00AM on 7/19/94, yielding 2000 epochs.

Usage

```
data("tensor")
```

Format

The format is: num [1:5, 1:2000, 1:6] 28.1 28.4 28.1 28.6 29.3 ...

References

Mark Rogers, Lei Li, and Stuart J Russell, "Multilinear dynamical systems for tensor time series," in *Advances in Neural Information Processing Systems (NIPS)*, 2013, pp. 2634–2642.

Examples

```
data(tensor)
```

Index

* **datasets**
 tensor, 5

err, 2

LTAR, 3

LTARpred, 4

Ltrans, 5

tensor, 5