

Package ‘phoenix’

March 12, 2024

Title The Phoenix Pediatric Sepsis and Septic Shock Criteria

Version 1.0.0

Description Implementation of the Phoenix and Phoenix-8 Sepsis Criteria as described in “Development and Validation of the Phoenix Criteria for Pediatric Sepsis and Septic Shock” by Sanchez-Pinto, Bennett, DeWitt, Russell et al. (2024) <[doi:10.1001/jama.2024.0196](https://doi.org/10.1001/jama.2024.0196)> (Drs. Sanchez-Pinto and Bennett contributed equally to this manuscript; Dr. DeWitt and Mr. Russell contributed equally to the manuscript) and “International Consensus Criteria for Pediatric Sepsis and Septic Shock” by Schlapbach, Watson, Sorce, Argent, et al. (2024) <[doi:10.1001/jama.2024.0179](https://doi.org/10.1001/jama.2024.0179)> (Drs Schlapbach, Watson, Sorce, and Argent contributed equally).

Depends R (>= 3.5.0)

License MIT + file LICENSE

Encoding UTF-8

URL <https://github.com/CU-DBMI-Peds/phoenix/>

BugReports <https://github.com/CU-DBMI-Peds/phoenix/issues>

Language en-us

LazyData true

Imports

LinkingTo

Suggests knitr, ggplot2, qwraps2 (>= 0.6.0), reticulate, rmarkdown

VignetteBuilder knitr

RoxygenNote 7.3.1

NeedsCompilation no

Author Peter DeWitt [aut, cre] (<<https://orcid.org/0000-0002-6391-0795>>),
Seth Russell [ctb] (<<https://orcid.org/0000-0002-2436-1367>>),
Meg Rebull [ctb] (<<https://orcid.org/0000-0003-0334-4223>>),
Tell Bennett [ctb] (<<https://orcid.org/0000-0003-1483-4236>>),
L. Nelson Sanchez-Pinto [ctb] (<<https://orcid.org/0000-0002-7434-6747>>)

Maintainer Peter DeWitt <peter.dewitt@cuanschutz.edu>

Repository CRAN

Date/Publication 2024-03-12 20:00:02 UTC

R topics documented:

phoenix	2
phoenix8	5
phoenix_cardiovascular	8
phoenix_coagulation	11
phoenix_endocrine	13
phoenix_hepatic	14
phoenix_immunologic	15
phoenix_neurologic	17
phoenix_renal	19
phoenix_respiratory	21
sepsis	23

Index [25](#)

phoenix	<i>The Phoenix Sepsis Score</i>
---------	---------------------------------

Description

The diagnostic Phoenix Sepsis Criteria based on four organ dysfunction scores, respiratory, cardiovascular, coagulation, and neurologic. A score of 2 or more indicates sepsis.

Usage

```
phoenix(
  pf_ratio,
  sf_ratio,
  imv,
  other_respiratory_support,
  vasoactives,
  lactate,
  map,
  platelets,
  inr,
  d_dimer,
  fibrinogen,
  gcs,
  fixed_pupils,
  age,
  data = parent.frame(),
  ...
)
```

Arguments

pf_ratio	numeric vector
sf_ratio	numeric vector
imv	invasive mechanical ventilation; numeric or integer vector, (0 = not intubated; 1 = intubated)
other_respiratory_support	other respiratory support; numeric or integer vector, (0 = no support; 1 = support)
vasoactives	an integer vector, the number of systemic vasoactive medications being administered to the patient
lactate	numeric vector with the lactate value in mmol/L
map	numeric vector, mean arterial pressure in mmHg
platelets	numeric vector for platelets counts in units of 1,000/uL (thousand per microliter)
inr	numeric vector for the international normalised ratio blood test
d_dimer	numeric vector for D-Dimer, units of mg/L FEU
fibrinogen	numeric vector units of mg/dL
gcs	integer vector; total Glasgow Comma Score
fixed_pupils	integer vector; 1 = bilaterally fixed pupil, 0 = otherwise
age	numeric vector age in months
data	a list, data.frame, or environment containing the input vectors
...	pass through

Details

The details of each of the four component scores are found in their respective help files.

Value

A data.frame with seven columns:

1. phoenix_respiratory_score
2. phoenix_cardiovascular_score
3. phoenix_coagulation_score
4. phoenix_neurologic_score
5. phoenix_sepsis_score
6. phoenix_sepsis An integer vector, 0 = not septic, 1 = septic (score greater or equal to 2)
7. phoenix_septic_shock An integer vector, 0 = not septic shock, 1 = septic shock (score greater or equal 2 and cardiovascular dysfunction)

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),
 - [phoenix_renal](#),
 - [phoenix_hepatic](#),

`vignette('phoenix')` for more details and examples.

Examples

```
# Using the example sepsis data set, read more details in the vignette
phoenix_scores <-
  phoenix(
    # respiratory
    pf_ratio = pao2 / fio2,
    sf_ratio = ifelse(spo2 <= 97, spo2 / fio2, NA_real_),
    imv = vent,
    other_respiratory_support = as.integer(fio2 > 0.21),
    # cardiovascular
    vasoactives = dobutamine + dopamine + epinephrine + milrinone + norepinephrine + vasopressin,
    lactate = lactate,
    age = age,
    map = dbp + (sbp - dbp)/3,
    # coagulation
    platelets = platelets,
    inr = inr,
    d_dimer = d_dimer,
    fibrinogen = fibrinogen,
    # neurologic
    gcs = gcs_total,
    fixed_pupils = as.integer(pupil == "both-fixed"),
    data = sepsis
  )

str(phoenix_scores)
```

phoenix8

The Phoenix 8 Sepsis Score

Description

The extended Phoenix criteria using a total eight organ systems. This is intended mostly for research as an extension of the Phoenix Sepsis Criteria which is based on four organ systems.

Usage

```
phoenix8(  
  pf_ratio,  
  sf_ratio,  
  imv,  
  other_respiratory_support,  
  vasoactives,  
  lactate,  
  map,  
  platelets,  
  inr,  
  d_dimer,  
  fibrinogen,  
  gcs,  
  fixed_pupils,  
  glucose,  
  anc,  
  alc,  
  creatinine,  
  bilirubin,  
  alt,  
  age,  
  data = parent.frame(),  
  ...  
)
```

Arguments

pf_ratio	numeric vector
sf_ratio	numeric vector
imv	invasive mechanical ventilation; numeric or integer vector, (0 = not intubated; 1 = intubated)
other_respiratory_support	other respiratory support; numeric or integer vector, (0 = no support; 1 = support)
vasoactives	an integer vector, the number of systemic vasoactive medications being administered to the patient

<code>lactate</code>	numeric vector with the lactate value in mmol/L
<code>map</code>	numeric vector, mean arterial pressure in mmHg
<code>platelets</code>	numeric vector for platelets counts in units of 1,000/uL (thousand per microliter)
<code>inr</code>	numeric vector for the international normalised ratio blood test
<code>d_dimer</code>	numeric vector for D-Dimer, units of mg/L FEU
<code>fibrinogen</code>	numeric vector units of mg/dL
<code>gcs</code>	integer vector; total Glasgow Comma Score
<code>fixed_pupils</code>	integer vector; 1 = bilaterally fixed pupil, 0 = otherwise
<code>glucose</code>	numeric vector; blood glucose measured in mg/dL
<code>anc</code>	absolute neutrophil count; a numeric vector; units of 1,000 cells per cubic millimeter
<code>alc</code>	absolute lymphocyte count; a numeric vector; units of 1,000 cells per cubic millimeter
<code>creatinine</code>	numeric vector; units of mg/dL
<code>bilirubin</code>	numeric vector; units of mg/dL
<code>alt</code>	alanine aminotransferase; a numeric vector; units of IU/L
<code>age</code>	numeric vector age in months
<code>data</code>	a list, data.frame, or environment containing the input vectors
<code>...</code>	pass through

Details

The Phoenix Sepsis Criteria is based on the score form respiratory, cardiovascular, coagulation, and neurologic. Phoenix 8 uses these four an endocrine, immunologic, renal, and hepatic. Details on the scoring for each of the eight component organ systems are found in the respective manual files.

Value

a data.frame with 12 integer columns.

1. `phoenix_respiratory_score`
2. `phoenix_cardiovascular_score`
3. `phoenix_coagulation_score`
4. `phoenix_neurologic_score`
5. `phoenix_sepsis_score`
6. `phoenix_sepsis` 0 = not septic; 1 = septic (`phoenix_sepsis_score` greater or equal 2)
7. `phoenix_septic_shock` 0 = no septic shock; 1 = septic shock (sepsis with cardiovascular dysfunction)
8. `phoenix_endocrine_score`
9. `phoenix_immunologic_score`
10. `phoenix_renal_score`

11. phoenix_hepatic_score
12. phoenix8_sepsis_score

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),
 - [phoenix_renal](#),
 - [phoenix_hepatic](#),

`vignette('phoenix')` for more details and examples.

Examples

```
# Using the example sepsis data set, read more details in the vignette
phoenix8_scores <-
  phoenix8(
    # respiratory
    pf_ratio = pao2 / fio2,
    sf_ratio = ifelse(spo2 <= 97, spo2 / fio2, NA_real_),
    imv = vent,
    other_respiratory_support = as.integer(fio2 > 0.21),
    # cardiovascular
    vasoactives = dobutamine + dopamine + epinephrine + milrinone + norepinephrine + vasopressin,
    lactate = lactate,
    age = age, # Also used in the renal assessment.
    map = dbp + (sbp - dbp)/3,
    # coagulation
    platelets = platelets,
    inr = inr,
    d_dimer = d_dimer,
    fibrinogen = fibrinogen,
    # neurologic
    gcs = gcs_total,
    fixed_pupils = as.integer(pupil == "both-fixed"),
```

```

# endocrine
  glucose = glucose,
# immunologic
  anc = anc,
  alc = alc,
# renal
  creatinine = creatinine,
# no need to specify age again
# hepatic
  bilirubin = bilirubin,
  alt = alt,
  data = sepsis
)

str(phoenix8_scores)

```

phoenix_cardiovascular

Phoenix Cardiovascular Score

Description

Generate the cardiovascular organ system dysfunction score as part of the diagnostic Phoenix Sepsis Criteria.

Usage

```

phoenix_cardiovascular(
  vasoactives = NA_integer_,
  lactate = NA_real_,
  age = NA_real_,
  map = NA_real_,
  data = parent.frame(),
  ...
)

```

Arguments

vasoactives	an integer vector, the number of systemic vasoactive medications being administered to the patient
lactate	numeric vector with the lactate value in mmol/L
age	numeric vector age in months
map	numeric vector, mean arterial pressure in mmHg
data	a list, data.frame, or environment containing the input vectors
...	pass through

Details

There were six systemic vasoactive medications considered when the Phoenix criteria was developed: dobutamine, dopamine, epinephrine, milrinone, norepinephrine, and vasopressin.

During development, the values used for map were taken preferentially from arterial measurement, then cuff measures, and provided values before approximating the map from blood pressure values via $DBP + 1/3 (SBP - DBP)$, where DBP is the diastolic blood pressure and SBP is the systolic blood pressure.

Value

a integer vector with values 0, 1, 2, 3, 4, 5, or 6.

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

Phoenix Cardiovascular Scoring

The Phoenix Cardiovascular score ranges from 0 to 6 points; 0, 1, or 2 points for each of systolic vasoactive medications, lactate, and MAP.

Systemic Vasoactive Medications

0 medications	0 points
1 medication	1 point
2 or more medications	2 points

Lactate

[0, 5)	0 points
[5, 11)	1 point
[11, Inf)	2 points

MAP

Age in [0, 1) months	[31, Inf) mmHg	0 points
	[17, 31) mmHg	1 point
	[0, 17) mmHg	2 points
Age in [1, 12) months	[39, Inf) mmHg	0 points
	[25, 39) mmHg	1 point
	[0, 25) mmHg	2 points
Age in [12, 24) months	[44, Inf) mmHg	0 points
	[31, 44) mmHg	1 point
	[0, 31) mmHg	2 points
Age in [24, 60) months	[45, Inf) mmHg	0 points
	[32, 45) mmHg	1 point

Age in [60, 144) months	[0, 32) mmHg	2 points
	[49, Inf) mmHg	0 points
	[36, 49) mmHg	1 point
Age in [144, 216] months	[0, 36) mmHg	2 points
	[52, Inf) mmHg	0 points
	[38, 52) mmHg	1 point
	[0, 38) mmHg	2 points

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),
 - [phoenix_renal](#),
 - [phoenix_hepatic](#),

`vignette('phoenix')` for more details and examples.

Examples

```
# using the example sepsis data set
phoenix_cardiovascular(
  vasoactives = dobutamine + dopamine + epinephrine + milrinone + norepinephrine + vasopressin,
  lactate = lactate,
  age = age,
  map = dbp + (sbp - dbp)/3,
  data = sepsis
)

# example data set to get all the possible scores
DF <-
  expand.grid(vasos = c(NA, 0:6),
             lactate = c(NA, 3.2, 5, 7.8, 11, 14),
             age = c(NA, 0.4, 1, 3, 12, 18, 24, 45, 60, 61, 144, 145),
             map = c(NA, 16:52))
```

```

DF$card <- phoenix_cardiovascular(vasos, lactate, age, map, DF)
head(DF)

# what if lactate is unknown for all records? - set the value either in the
# data object or the argument value to NA
DF2 <-
  expand.grid(vasos = c(NA, 0:6),
             age = c(NA, 0.4, 1, 3, 12, 18, 24, 45, 60, 61, 144, 145),
             map = c(NA, 16:52))
DF2$card <- phoenix_cardiovascular(vasos, lactate = NA, age, map, DF2)

DF3 <-
  expand.grid(vasos = c(NA, 0:6),
             lactate = NA,
             age = c(NA, 0.4, 1, 3, 12, 18, 24, 45, 60, 61, 144, 145),
             map = c(NA, 16:52))
DF3$card <- phoenix_cardiovascular(vasos, lactate, age, map, DF3)

identical(DF2$card, DF3$card)

```

phoenix_coagulation *Phoenix Coagulation Score*

Description

Applies the Phoenix coagulation organ dysfunction scoring to a set of inputs.

Usage

```

phoenix_coagulation(
  platelets = NA_real_,
  inr = NA_real_,
  d_dimer = NA_real_,
  fibrinogen = NA_real_,
  data = parent.frame(),
  ...
)

```

Arguments

platelets	numeric vector for platelets counts in units of 1,000/uL (thousand per microliter)
inr	numeric vector for the international normalised ratio blood test
d_dimer	numeric vector for D-Dimer, units of mg/L FEU
fibrinogen	numeric vector units of mg/dL
data	a list, data.frame, or environment containing the input vectors
...	pass through

Value

a integer vector with values 0, 1, or 2

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

Phoenix Coagulation Scoring

1 point each for platelets < 100 K/micro liter, INR > 1.3, D-dimer > 2 mg/L FEU, and fibrinogen < 100 mg/dL, with a max total score of 2.

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),
 - [phoenix_renal](#),
 - [phoenix_hepatic](#),

`vignette('phoenix')` for more details and examples.

Examples

```
# using the example data set
phoenix_coagulation(
  platelets = platelets,
  inr = inr,
  d_dimer = d_dimer,
  fibrinogen = fibrinogen,
  data = sepsis
)

# build a data.frame with values for all possible combinations of values
# leading to all possible coagulation scores.
DF <-
  expand.grid(plts = c(NA, 20, 100, 150),
             inr = c(NA, 0.2, 1.3, 1.8),
             ddmr = c(NA, 1.7, 2.0, 2.8),
             fib = c(NA, 88, 100, 120))
```

```
DF$coag <- phoenix_coagulation(plts, inr, ddmr, fib, DF)
DF
```

phoenix_endocrine *Phoenix Endocrine Score*

Description

Assess the Phoenix endocrine organ dysfunction score. This score is not part of the Phoenix score, only part of the Phoenix-8 score.

Usage

```
phoenix_endocrine(glucose = NA_real_, data = parent.frame(), ...)
```

Arguments

glucose	numeric vector; blood glucose measured in mg/dL
data	a list, data.frame, or environment containing the input vectors
...	pass through

Value

a integer vector with values 0 or 1

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

Phoenix Endocrine Scoring

The endocrine dysfunction score is based on blood glucose with one point for levels < 50 mg/dL or > 150 mg/dL.

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and

- phoenix_endocrine,
- phoenix_immunologic,
- phoenix_renal,
- phoenix_hepatic,

vignette('phoenix') for more details and examples.

Examples

```
# using the example sepsis data set
endo_example <- sepsis[c("pid", "glucose")]
endo_example$score <- phoenix_endocrine(glucose, data = sepsis)
endo_example

# example data set to get all the possible endocrine scores
DF <- data.frame(glc = c(NA, 12, 50, 55, 100, 150, 178))
phoenix_endocrine(glucose = glc, data = DF)
```

phoenix_hepatic	<i>Phoenix Hepatic Score</i>
-----------------	------------------------------

Description

Apply the Phoenix Hepatic scoring based on total bilirubin and ALT.

Usage

```
phoenix_hepatic(
  bilirubin = NA_real_,
  alt = NA_real_,
  data = parent.frame(),
  ...
)
```

Arguments

bilirubin	numeric vector; units of mg/dL
alt	alanine aminotransferase; a numeric vector; units of IU/L
data	a list, data.frame, or environment containing the input vectors
...	pass through

Value

a integer vector with values 0 or 1

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

Phoenix Hepatic Scoring

1 point for total bilirubin greater or equal to 4 mg/dL and/or ALT strictly greater than 102 IU/L.

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),
 - [phoenix_renal](#),
 - [phoenix_hepatic](#),

`vignette('phoenix')` for more details and examples.

Examples

```
# using the example sepsis data set
hep_example <- sepsis[c("pid", "bilirubin", "alt")]
hep_example$score <- phoenix_hepatic(bilirubin, alt, sepsis)
hep_example

# example data set with all possible hepatic scores
DF <- expand.grid(bil = c(NA, 3.2, 4.0, 4.3), alt = c(NA, 99, 102, 106))
phoenix_hepatic(bilirubin = bil, alt = alt, data = DF)
```

phoenix_immunologic *Phoenix Immunologic Score*

Description

Apply the Phoenix immunologic scoring based on ANC and ALC. This is only part of Phoenix-8 and not Phoenix.

Usage

```
phoenix_immunologic(anc = NA_real_, alc = NA_real_, data = parent.frame(), ...)
```

Arguments

anc	absolute neutrophil count; a numeric vector; units of 1,000 cells per cubic millimeter
alc	absolute lymphocyte count; a numeric vector; units of 1,000 cells per cubic millimeter
data	a list, data.frame, or environment containing the input vectors
...	pass through

Value

a integer vector with values 0 or 1

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

Phoenix Immunologic Scoring

1 point if ANC < 500 or ALC < 1000 cells per cubic millimeter.

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),
 - [phoenix_renal](#),
 - [phoenix_hepatic](#),

`vignette('phoenix')` for more details and examples.

Examples

```
# using the example sepsis data set
immu_example <- sepsis[c("pid", "anc", "alc")]
immu_example$score <- phoenix_immunologic(anc, alc, sepsis)
immu_example

# using the example sepsis data set
```



```

hep_example <- sepsis[c("pid", "bilirubin", "alt")]
hep_example$score <- phoenix_hepatic(bilirubin, alt, sepsis)
hep_example

# example data set with all possible hepatic scores
DF <- expand.grid(anc = c(NA, 200, 500, 600), alc = c(NA, 500, 1000, 2000))
phoenix_immunologic(anc = anc, alc = alc, data = DF)

```

phoenix_neurologic *Phoenix Sepsis Neurological Score*

Description

Assessment of neurologic dysfunction based on Glasgow Coma Scale (GCS) and pupil reactivity. This score is part of the diagnostic Phoenix Sepsis criteria and Phoenix 8 Sepsis criteria.

Usage

```

phoenix_neurologic(
  gcs = NA_integer_,
  fixed_pupils = NA_real_,
  data = parent.frame(),
  ...
)

```

Arguments

gcs	integer vector; total Glasgow Comma Score
fixed_pupils	integer vector; 1 = bilaterally fixed pupil, 0 = otherwise
data	a list, data.frame, or environment containing the input vectors
...	pass through

Details

Missing values will map to a value of 0 as was done when developing the Phoenix criteria. Note that this is done on a input by input basis. That is, if pupil reactivity is missing but GCS (total) is 9, then the neurologic dysfunction score is 1.

GCS total is the sum of a score based on eyes, motor control, and verbal responsiveness.

Eye response:

1. no eye opening,
2. eye opening to pain,
3. eye opening to sound,
4. eyes open spontaneously.

Verbal response:

1. no verbal response,
2. incomprehensible sounds,
3. inappropriate words,
4. confused,
5. orientated

Motor response:

1. no motor response,
2. abnormal extension to pain,
3. abnormal flexion to pain,
4. withdrawal from pain,
5. localized pain,
6. obeys commands

Value

an integer vector with values 0, 1, or 2. As with all Phoenix organ dysfunction scores, missing input values map to scores of zero.

Phoenix Neurological Scoring

Bilaterally fixed pupil	2 points
Glasgow Coma Score (total) less or equal 10	1 point
Reactive pupils and GCS > 10	0 point

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),

- phoenix_renal,
- phoenix_hepatic,

vignette('phoenix') for more details and examples.

Examples

```
# using the example sepsis data set
phoenix_neurologic(
  gcs = gcs_total,
  fixed_pupils = as.integer(pupil == "both-fixed"),
  data = sepsis
)

# build an example data set with all possible neurologic scores
DF <- expand.grid(gcs = c(3:15, NA), pupils = c(0, 1, NA))
DF$target <- 0L
DF$target[DF$gcs <= 10] <- 1L
DF$target[DF$pupils == 1] <- 2L
DF$current <- phoenix_neurologic(gcs, pupils, DF)
stopifnot(identical(DF$target, DF$current))
DF
```

phoenix_renal	<i>Phoenix Renal Score</i>
---------------	----------------------------

Description

Apply the Phoenix renal organ dysfunction score based on age adjusted creatinine levels.

Usage

```
phoenix_renal(
  creatinine = NA_real_,
  age = NA_real_,
  data = parent.frame(),
  ...
)
```

Arguments

creatinine	numeric vector; units of mg/dL
age	numeric vector age in months
data	a list, data.frame, or environment containing the input vectors
...	pass through

Value

a integer vector with values 0, 1, or 2

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

Phoenix Renal Scoring

Age in [0, 1) months	creatinine [0, 0.8) mg/dL	0 points
	creatinine [0.8, Inf) mg/dL	1 point
Age in [1, 12) months	creatinine in [0, 0.3) mg/dL	0 points
	creatinine in [0.3, Inf) mg/dL	1 point
Age in [12, 24) months	creatinine in [0, 0.4) mg/dL	0 points
	creatinine in [0.4, Inf) mg/dL	1 point
Age in [24, 60) months	creatinine in [0, 0.6) mg/dL	0 points
	creatinine in [0.6, Inf) mg/dL	1 point
Age in [60, 144) months	creatinine in [0, 0.7) mg/dL	0 points
	creatinine in [0.7, Inf) mg/dL	1 point
Age in [144, 216] months	creatinine in [0, 1.0) mg/dL	0 points
	creatinine in [1.0, Inf) mg/dL	1 point

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),
 - [phoenix_renal](#),
 - [phoenix_hepatic](#),

vignette('phoenix') for more details and examples.

Examples

```
# using the example sepsis data set
renal_example <- sepsis[c("creatinine", "age")]
renal_example$score <- phoenix_renal(creatinine, age, sepsis)
renal_example

# build an example data set with all possible neurologic scores
DF <- expand.grid(age = c(NA, 0.4, 1, 3, 12, 18, 24, 45, 60, 61, 144, 145),
                 creatinine = c(NA, seq(0.0, 1.1, by = 0.1)))
DF$card <- phoenix_renal(age = age, creatinine = creatinine, data = DF)

head(DF)
```

phoenix_respiratory *Phoenix Respiratory Score*

Description

Apply the Phoenix Respiratory Scoring rubric to a data set. The respiratory score is part of the diagnostic Phoenix Sepsis criteria and the diagnostic Phoenix 8 Sepsis criteria.

Usage

```
phoenix_respiratory(
  pf_ratio = NA_real_,
  sf_ratio = NA_real_,
  imv = NA_integer_,
  other_respiratory_support = NA_integer_,
  data = parent.frame(),
  ...
)
```

Arguments

pf_ratio	numeric vector
sf_ratio	numeric vector
imv	invasive mechanical ventilation; numeric or integer vector, (0 = not intubated; 1 = intubated)
other_respiratory_support	other respiratory support; numeric or integer vector, (0 = no support; 1 = support)
data	a list, data.frame, or environment containing the input vectors
...	pass through

Details

pf_ratio is the ratio of partial pressure of oxygen in arterial blood (PaO2) to the fraction of inspiratory oxygen concentration (FiO2).

sf_ratio is a non-invasive surrogate for pf_ratio using pulse oximetry (SpO2) instead of invasive PaO2.

Important Note: when the Phoenix Sepsis criteria was developed there is a requirement that SpO2 < 97 in order for the sf_ratio to be valid. That assumption is not checked in this code and it is left to the end user to account for this when building the sf_ratio vector.

imv Invasive mechanical ventilation - integer vector where 0 = not intubated and 1 = intubated.

other_respiratory_support other respiratory support such as receiving oxygen, high-flow, non-invasive positive pressure, or imv.

Value

a integer vector with values 0, 1, 2, or 3.

As with all other Phoenix organ system scores, missing values in the data set will map to a score of zero - this is consistent with the development of the criteria.

Phoenix Respiratory Scoring

0 points

pf_ratio >= 400 and sf_ratio >= 292

1 point

(pf_ratio < 400 or sf_ratio < 292) and any respiratory support

2 points

(pf_ratio < 200 or sf_ratio < 292)

References

See reference details in [phoenix-package](#) or by calling `citation('phoenix')`.

See Also

- [phoenix](#) for generating the diagnostic Phoenix Sepsis score based on the four organ systems:
 - [phoenix_cardiovascular](#),
 - [phoenix_coagulation](#),
 - [phoenix_neurologic](#),
 - [phoenix_respiratory](#),
- [phoenix8](#) for generating the diagnostic Phoenix 8 Sepsis criteria based on the four organ systems noted above and
 - [phoenix_endocrine](#),
 - [phoenix_immunologic](#),
 - [phoenix_renal](#),
 - [phoenix_hepatic](#),

`vignette('phoenix')` for more details and examples.

Examples

```
# Using the provided example data set:
phoenix_respiratory(
  pf_ratio = pao2 / fio2,
  sf_ratio = spo2 / fio2,
  imv      = vent,
  other_respiratory_support = as.integer(fio2 > 0.21),
  data = sepsis
)

# A set of values that will get all possible respiratory scores:
DF <- expand.grid(
  pfr = c(NA, 500, 400, 350, 200, 187, 100, 56),
  sfr = c(NA, 300, 292, 254, 220, 177, 148, 76),
  vent = c(NA, 0, 1),
  o2 = c(NA, 0, 1)
)

phoenix_respiratory(
  pf_ratio = pfr,
  sf_ratio = sfr,
  imv = vent,
  other_respiratory_support = o2,
  data = DF
)
```

sepsis

sepsis

Description

A fully synthetic data set with variables need for examples and documentation of the Phoenix Sepsis Criteria.

Usage

```
sepsis
```

Format

a data.frame with 20 rows and 27 columns

[, 1]	pid	patient identification number
[, 2]	age	age in months
[, 3]	fio2	fraction of inspired oxygen
[, 4]	pao2	partial pressure of oxygen in arterial blood (mmHg)

[, 5]	spo2	pulse oximetry
[, 6]	vent	indicator for invasive mechanical ventilation
[, 7]	gcs_total	total Glasgow Coma Scale
[, 8]	pupil	character vector reporting if pupils are reactive or fixed.
[, 9]	platelets	platelets measured in 1,000 / microliter
[, 10]	inr	international normalized ratio
[, 11]	d_dimer	D-dimer; units of mg/L FEU
[, 12]	fibrinogen	units of mg/dL
[, 13]	dbp	diagnostic blood pressure (mmHg)
[, 14]	sbp	systolic blood pressure (mmHg)
[, 15]	lactate	units of mmol/L
[, 16]	dobutamine	indicator for receiving systemic dobutamine
[, 17]	dopamine	indicator for receiving systemic dopamine
[, 18]	epinephrine	indicator for receiving systemic epinephrine
[, 19]	milrinone	indicator for receiving systemic milrinone
[, 20]	norepinephrine	indicator for receiving systemic norepinephrine
[, 21]	vasopressin	indicator for receiving systemic vasopressin
[, 22]	glucose	units of mg/dL
[, 23]	anc	units of 1,000 cells per cubic millimeter
[, 24]	alc	units of 1,000 cells per cubic millimeter
[, 25]	creatinine	units of mg/dL
[, 26]	bilirubin	units of mg/dL
[, 27]	alt	units of IU/L

Index

* datasets

sepsis, 23

phoenix, 2, 4, 7, 10, 12, 13, 15, 16, 18, 20, 22
phoenix8, 4, 5, 7, 10, 12, 13, 15, 16, 18, 20, 22
phoenix_cardiovascular, 4, 7, 8, 10, 12, 13,
15, 16, 18, 20, 22
phoenix_coagulation, 4, 7, 10, 11, 12, 13,
15, 16, 18, 20, 22
phoenix_endocrine, 4, 7, 10, 12, 13, 14–16,
18, 20, 22
phoenix_hepatic, 4, 7, 10, 12, 14, 14, 15, 16,
19, 20, 22
phoenix_immunologic, 4, 7, 10, 12, 14, 15,
15, 16, 18, 20, 22
phoenix_neurologic, 4, 7, 10, 12, 13, 15, 16,
17, 18, 20, 22
phoenix_renal, 4, 7, 10, 12, 14–16, 19, 19,
20, 22
phoenix_respiratory, 4, 7, 10, 12, 13, 15,
16, 18, 20, 21, 22

sepsis, 23